

A close-up, high-contrast photograph of a tire tread pattern, showing various grooves and sipes. The image is dark, with the tread pattern highlighted in a lighter shade, creating a sense of depth and texture. The pattern consists of several parallel longitudinal grooves, with smaller sipes and wavy patterns in the grooves.

HYPERICH

ALL STEEL RADIAL TIRE
PRODUCT MANUAL



HA31



Wear resistant



Tear resistant



Anti-puncture



Regional Urban Roads

- Excellent wear resistance, tear resistance and puncture resistance.
- Optimize structural design, better bearing performance, reduce heat generation, and extend service life.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
325/95R24	22	162/160	K	4750/4500	850	9. 00	325	1228	17. 0
12. 00R24	22	162/160	K	4750/4500	850	8. 5	315	1226	17. 0



HA32




Wear resistant



Prevents uneven wear



Durability



Long Haul Regional Urban Roads

- The closure design of shoulder pattern improves the anti-eccentric wear performance.
- The formula of wear resistant rubber, prolongs service life.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
315/80R22. 5	20	157/154	M	4125/3750	900	9. 00	312	1076	14. 5



HA33




Wear resistant



Anti wet slip



Anti-puncture



Regional Urban Roads

- Unique formula design provides tires with excellent puncture resistance, wet skid resistance and wear resistance.
- Optimize structural design, improve tire bearing capacity, reduce heat generation and increase service life.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	M	3250/3000	930	8.25	279	1054	14.0



HA36




Wear resistant



Anti wet slip



Prevents uneven wear



Long Haul Regional Urban Roads

- Excellent wear resistance, deepened pattern design, highly improve tire wear resistance.
- Shoulder pattern close design can effectively improve the eccentric wear problem and prolong the service life.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12R22.5	18	152/149	L	3550/3250	930	9.00	300	1085	17.0



HA35




Tear resistant



Anti-puncture



Heat dissipation



Long Haul Regional Urban Roads

- Excellent anti-tear, anti impact and fatigue performance.
- Classic three-lined pattern and open shoulder design, low heat build-up.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
315/80R22.5	20	157/154	M	4125/3750	900	9.00	312	1076	14.5
325/95R24	22	162/160	K	4750/4500	850	9.00	325	1228	16.0
13R22.5	18	154/151	K	3750/3450	830	9.75	320	1124	16.0
12R22.5	18	152/149	K	3550/3250	930	9.00	300	1085	14.5
12.00R24	22	162/160	K	4750/4500	850	8.5	315	1226	16.0
11R22.5	18	149/146	K	3250/3000	930	8.25	279	1054	14.5
11R24.5	16	149/146	M	3250/3000	830	8.25	279	1104	16.0
12.00R20	20	156/153	K	4000/3650	900	8.5	315	1125	16.5
11.00R20	18	152/149	K	3550/3250	930	8.0	293	1085	16.0
10.00R20	18	149/146	K	3250/3000	930	7.5	278	1054	15.5
9.00R20	16	144/142	K	2800/2650	900	7.0	259	1019	15.0
8.25R20	16	139/137	K	2430/2300	930	6.5	236	974	13.5
8.25R16LT	16	128/124	K	1800/1600	770	6.50H	235	855	13.0
7.50R16LT	16	125/121	K	1650/1450	870	6.00G	215	805	12.0
7.00R16LT	14	118/114	K	1320/1180	770	5.50F	200	775	12.0
6.50R16LT	12	110/105	K	1060/925	670	5.50F	185	750	11.5



HF11




Wear resistant



Low heat build-up



Tear resistant



Long Haul Regional Urban Roads

- Excellent wear resistance , anti-wear and low heat-up performance.

- Excellent high speed performance, more durable and comfortable.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
315/80R22.5	20	157/154	M	4125/3750	900	9.00	312	1076	14.5
295/80R22.5	18	152/149	M	3550/3250	900	9.00	298	1044	14.5



HF13




Wear resistant



Anti wet slip



Comfort



Long Haul Regional Urban Roads

- Excellent wear resistance and wet skid resistance.
- Excellent high-speed and comfortable performance.
- Low rolling resistance coefficient, less fuel consumption.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
7.50R16LT	16	125/121	K	1650/1450	870	6.00G	215	805	13.0
7.00R16LT	14	118/114	K	1320/1180	770	5.50F	200	775	12.5



HF12




Wear resistant



Anti wet slip



Fuel economical



Long Haul Regional Urban Roads

- Excellent wear resistance performance, anti-slip, more comfortable.

- Excellent high-speed performance, low rolling resistance, fuel economical.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
295/80R22.5	18	152/149	L	3550/3250	900	9.00	298	1044	14.5
315/80R22.5	20	157/154	L	4125/3750	900	9.00	312	1076	14.5
215/75R17.5	18	135/133	M	2180/2060	860	6.00	211	767	13.0
235/75R17.5	18	143/141	K	2725/2575	860	6.75	233	797	13.5



HS15




Wear resistant



Tear resistant



Low heat build-up



Long Haul Regional


- Excellent wear resistance, tear resistance and low heat generation performance.

- Excellent structure design, ensuring the loading capacity & comfort performance, and preventing eccentric wear.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
385/65R22.5	22	162	K	4750	900	11.75	389	1072	16.0



HS16




Long Haul Regional

- Excellent wear resistance, tear resistance and low heat generation performance.
- Excellent structure design, ensuring the loading capacity & comfort performance, and preventing eccentric wear.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
385/65R22.5	22	162	K	4750	900	11.75	389	1072	16.0



HF17




Long Haul Regional

- Excellent wear resistance, tear resistance and reduce heat generation.
- Excellent structural design to ensure loading capacity and comfort, anti-eccentric wear.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	M	3250/3000	930	8.25	279	1054	16.0
11R24.5	16	149/146	M	3250/3000	830	8.25	279	1104	16.0
245/70R19.5	18	141/140	L	2575/2500	930	7.50	248	839	14.0
245/70R17.5	18	134/132	K	2120/2000	900	7.50	248	789	14.0
275/70R22.5	16	144/141	M	2800/2575	830	8.25	276	958	16.5
275/80R22.5	18	149/146	L	3250/3000	900	8.25	276	1012	15.5
295/80R22.5	18	152/149	M	3550/3250	900	9.00	298	1044	14.5



HF18




Long Haul Regional Urban Roads

- Excellent wear and wet skid resistance.
- Excellent load capacity.
- Reinforced bead structure design provides excellent bead performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
265/70R19.5	18	143/141	J	2725/2575	860	7.50	262	867	13.0
295/75R22.5	16	146/143	M	3000/2725	830	9.00	298	1014	15.0
295/80R22.5	18	152/149	L	3550/3250	900	9.00	298	1044	17.5
315/70R22.5	20	154/151	L	3750/3450	930	9.00	312	1014	15.0
9.5R17.5	18	143/141	J	2725/2575	875	6.75	240	842	13.5



HF22



Long Haul Regional Urban Roads

- Excellent wear resistance, tear resistance and reduce heat generation.
- Excellent high-speed performance, durability and comfort.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
13R22.5	18	154/151	L	3750/3450	830	9.75	320	1124	15.0



HF23




Wear resistant



Low heat build-up



Prevents uneven wear



Long Haul Regional

- Excellent wear resistance, tear resistance and reduce heat generation.

- Excellent structural design to ensure loading capacity and comfort, anti-eccentric wear.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
295/60R22.5	18	150/147	K	3350/3075	900	9.00	292	926	16.5



HF25




Wear resistant



Anti wet slip



Fuel economical



Long Haul Regional Urban Roads

- Excellent wear resistance performance, anti-slip, more comfortable.

- Excellent high-speed performance, low rolling resistance, fuel economical.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12R22.5	18	152/149	L	3550/3250	930	9.00	300	1085	15.0



HF26




Wear resistant



Anti wet slip



Fuel economical



Long Haul Regional Urban Roads

- Excellent wear resistance, anti-skid and comfortable.

- Excellent high-speed performance, low rolling resistance, and more fuel-efficient.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	M	3250/3000	930	8.25	279	1054	16.0
295/80R22.5	18	152/149	L	3550/3250	900	9.00	298	1044	14.5
275/70R22.5	16	144/141	M	2800/2575	830	8.25	276	958	16.5
275/80R22.5	18	149/146	L	3250/3000	900	8.25	276	1012	15.5



HF27




Wear resistant



Anti wet slip



High-speed performance



Long Haul Regional

- Excellent wear resistant and anti-slip performance, more comfortable.

- Excellent high speed performance and durability.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	M	3250/3000	930	8.25	279	1054	14.5



HF28




Wear resistant



Low heat build-up



Prevents uneven wear



Long Haul Regional Urban Roads

- Excellent wear resistance, deepen pattern design, highly improve tire wear resistance.

- Shoulder pattern close design can effectively improve the eccentric wear problem and prolong the service life.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12R22.5	18	152/149	L	3550/3250	930	9.00	300	1085	15.0



HD55




Wear resistant



Anti wet slip



Drivability



Long Haul Regional Urban Roads

- Excellent wear resistance, highly improve tire wear resistance.

- Unique pattern design provides excellent wet skid resistance, strong braking and driving performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	L	3250/3000	930	8.25	279	1054	22.0
11R22.5	18	149/146	L	3250/3000	930	8.25	279	1054	24.0
11R24.5	16	149/146	L	3250/3000	830	8.25	279	1104	22.0
295/75R22.5	16	146/143	L	3000/2725	830	9.00	298	1014	20.0



HD56




Tear resistant



Load-bearing type



Drivability



Regional Urban Roads

- Excellent tear resistance and loading capacity.

- Optimum angle groove design can provide sufficient driving force, and maintain good handling performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R24.5	16	149/146	L	3250/3000	830	8.25	279	1104	20.0



HD57




Tear resistant



Grip



Drivability



Mixed Road

- Perfect cutting resistance and tear resistance.
- Excellent gripping and driving performance.
- Strong structure of carcass, improving bearing capacity.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
295/80R22.5	18	152/149	F	3550/3250	900	9.00	298	1044	22.0
325/95R24	22	162/160	F	4750/4500	850	9.00	325	1228	20.0
12.00R24	22	162/160	F	4750/4500	850	8.5	315	1226	20.0



HD58




Wear resistant



Low heat build-up



Anti wet slip



Long Haul Regional Urban Roads

- Excellent wear resistant & anti-slip performance, low heat build-up.

- Excellent anti-tear and impact and fatigue resistance performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
265/70R19.5	18	143/141	J	2725/2575	860	7.50	262	867	15.0
9.5R17.5	18	143/141	J	2725/2575	875	6.75	240	842	13.5



HD76




Wear resistant



Low heat build-up



Tear resistant



Long Haul Regional Urban Roads

- Excellent anti-wear and anti-tear performance, low heat build up.

- Excellent high speed performance and durability.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
295/80R22.5	18	152/149	L	3550/3250	900	9.00	298	1044	18.0
315/70R22.5	20	154/151	L	3750/3450	930	9.00	312	1014	20.0



HD78




Wear resistant



Anti wet slip



Heat dissipation



Long Haul Regional Urban Roads

- Good wear resistance, heat dissipation and wet skid resistance.

- Excellent high-speed and durable performance.

- Reinforced bead structure design, providing excellent load bearing performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12.00R20	20	156/153	K	4000/3650	900	8.5	315	1125	18.0
11.00R20	18	152/149	K	3550/3250	930	8.0	293	1085	18.0
10.00R20	18	149/146	K	3250/3000	930	7.5	278	1054	17.0
9.00R20	16	144/142	K	2800/2650	900	7.0	259	1019	16.0
13R22.5	18	154/151	K	3750/3450	830	9.75	320	1124	18.0



HD79




Wear resistant



Anti-puncture



Load-bearing type



Regional Urban Roads


- Excellent load-carrying properties.

- Optimized tire structure design, improved load performance for combined use of the tire.
- Excellent tear resistance, puncture resistance and wear resistance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
13R22.5	18	154/151	K	3750/3450	830	9.75	320	1124	21.0
11R22.5	18	149/146	K	3250/3000	930	8.25	279	1054	18.0



HD82




Long Haul Regional Urban Roads

- Strong driving and braking force.
- Open shoulder pattern design for better heat dissipation.
- Excellent wear and wet skid resistance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
13R22.5	18	154/151	K	3750/3450	830	9.75	320	1124	18.0
11R22.5	18	149/146	K	3250/3000	930	8.25	279	1054	18.0



HD83




Regional Urban Roads

- Enhanced loading performance, tear resistance, puncture resistance.
- Optimized tire structure and improved the performance of dual installing.
- The driving effect is better during heavy loading with the speed of 70km/h or less.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12.00R20	20	156/153	F	4000/3650	900	8.5	315	1125	19.5
11.00R20	18	152/149	F	3550/3250	930	8.0	293	1085	18.5



HD86




Long Haul Regional Urban Roads

- Strong driving force and braking force.
- Open shoulder pattern, better heat dissipation performance.
- Excellent anti-wear and anti-slip performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
295/80R22.5	18	152/149	L	3550/3250	900	9.00	298	1044	18.0
315/80R22.5	20	157/154	K	4125/3750	900	9.00	312	1076	18.0



HD87



Regional Urban Roads

- Excellent wear resistance, tear resistance and reduce heat generation.
- Excellent high-speed performance and durability.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
11R22.5	18	149/146	L	3250/3000	930	8.25	279	1054	18.0



HD88




Wear resistant



Tear resistant



Drivability



Regional Urban Roads

- Excellent driving force and anti-wear performance.
- Excellent durability, low heat dissipation and anti-wear performance.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12R22.5	18	152/149	K	3550/3250	930	9.00	300	1085	18.0
315/80R22.5	20	157/154	L	4125/3750	900	9.00	312	1076	20.0



HD89




Anti-puncture



Anti wet slip



Load-bearing type



Mining areas and other bad road conditions and urban construction waste transportation

- Optimize tyre structure design to increase load capacity.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12R22.5	18	152/149	F	3550/3250	930	9.00	300	1085	22.0

HYPERICH

TRUCK&BUS RADIAL TYRE PRODUCT



HM96




Load-bearing type



Tear resistant



Anti-puncture



Non paved pavement in mining area

- Excellent heavy-loading performance, better adapt to harsh road conditions.
- Special formula for mining to improve the performance of puncture resistance and tear resistance.
- The driving performance is better during heavy loading with the speed of 40km/h or less.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12.00R20	20	156/153	D	4000/3650	900	8.5	315	1136	23.0
11.00R20	18	152/149	D	3550/3250	930	8.0	293	1096	22.5



HM97




Load-bearing type



Tear resistant



Anti-puncture



Non paved pavement in mining area

- Excellent heavy-loading performance, better adapt to harsh road conditions.
- Special formula for mining to improve the performance of puncture resistance and tear resistance.
- The driving performance is better during heavy loading with the speed of 40km/h or less.

SIZE	PR	LOAD INDEX SINGLE / DUAL	SPEED INDEX	LOAD CAPACITY SINGLE / DUAL	PRESSURE KPA	STANDARD RIM INCH	SECTION WIDTH MM	OVERALL DIAMETER MM	TREAD DEPTH MM
12.00R20	20	156/153	D	4000/3650	900	8.5	315	1136	25.0
11.00R20	18	152/149	D	3550/3250	930	8.0	293	1096	24.0
10.00R20	18	149/146	D	3250/3000	930	7.5	278	1065	23.0
9.00R20	16	144/142	D	2800/2650	900	7.0	259	1030	22.0
8.25R20	16	139/137	D	2430/2300	930	6.5	236	986	21.5
8.25R16LT	16	128/124	D	1800/1600	770	6.50H	235	865	20.5
7.50R16LT	16	125/121	D	1650/1450	870	6.00G	215	815	20.0

SKYPOWER
QINGDAO SKYPOWER TIRE TECHNOLOGY CO.,LTD

Website: www.skypowertire.com